



Countertop Water Filter

- ✦ Removes all pathogenic bacteria*
- ✦ Reduces heavy metal ions
- ✦ Keeps the minerals and microelements in water
- ✦ Reduces residual chlorine
- ✦ Reduces organic pollutants
- ✦ Supplies safe and health drinkable water

*99.9999% Escherichia coli, Staphylococcus aureus, Salmonella typhi, Vibrio cholerae, Pseudomonas aeruginosa.



HF121

Technical Data

Cartridge: 0.1micron dual ceramic membrane cartridge
 Output: Approx. 4L/min at 0.2Mpa (29 psi)
 Cartridge Capacity: Approx. 10,000 liters (depending on water condition)
 Working Pressure: 0.1~0.4MPa
 Operating Temperature: 5°C~45°C
 Weight: Approx. 860g
 Dimensions: 14.2×10.1×32cm

Features

Removes bacteria entirely
 Inhibits bacteria growth



HF122

Technical Data

Cartridge:
 ① Composite Pre Filter
 ② 0.1micron dual ceramic membrane cartridge
 Output: Approx. 2L/min at 0.2Mpa (29 psi)
 Cartridge Capacity: Approx. 10,000 liters (depending on water condition)
 Working Pressure: 0.1~0.4MPa
 Operating Temperature: 5°C~45°C
 Weight: Approx. 1.6Kg
 Dimensions: 23×10.1×32cm

Features

For a better taste



HF123

Technical Data

Cartridge:
 ① Composite Pre Filter
 ② Special function cartridge: Exchange resin
 ③ 0.1micron dual ceramic membrane cartridge
 Output: Approx. 2L/min at 0.2Mpa (29 psi)
 Cartridge Capacity: Approx. 10,000 liters (depending on water condition)
 Working Pressure: 0.1~0.4MPa
 Operating Temperature: 5°C~45°C
 Weight: Approx. 2.1Kg
 Dimensions: 30×10.1×32cm

Features

Decreases the scale and the hardness with exchange resin cartridge

Model	Inner box packing size (L×W×H)cm	Outer carton packing size (L×W×H)cm	N.W/G.W (kg)	Qty in 20' Gp	Qty in 40' Gp
HF121	14.2×10.1×32cm(1pcs)	47.5×36×34.5cm(12pcs)	11.9/12.9	5,000	11,000
HF122	23.6×10×33.5cm(1pcs)	49×41.5×35cm(6pcs)	11.4/12.4	2,000	5,000
HF123	33×10.5×33.5cm(1pcs)	53×34×35cm(5pcs)	13.0/14.0	1,900	4,300



Countertop Water Filter (Stainless steel)



HF122S

Technical Data

Cartridge: Pre composite filter+ Post composite filter
 Output: Approx. 4L/min at 0.2Mpa (29 psi)
 Cartridge Capacity: Approx. 4,000 liters (depending on water condition)
 Working Pressure: 0.1~0.6MPa
 Operating Temperature: 5°C~45°C
 Weight: 2.8Kg
 Dimensions: 24.5×6.5×28cm

Features

99.99% bacteria removing efficiency
 Non-clean filter cartridge
 Inhibits bacteria growth
 Elegant stainless steel appearance
 For a better taste

Gravity Water Filter



HF521-HF524

Technical Data

Cartridge: 0.1µm dual ceramic membrane cartridge (At most 4 cartridges)
 Output: 3-5L/h plus cartridge quantity (200mm hydrostatic pressure)
 Cartridge Capacity: Approx. 10,000 liters plus cartridge quantity
 (depending on water condition)
 Operating Temperature: 5°C~45°C
 Weight: Approx. 3.5Kg
 Dimensions: 30×30×60cm

Features

Remove bacteria entirely
 Inhibits bacteria growth
 Cleanable filter cartridge
 Suit for : household using, household using with dispenser, outdoor using

Model	Carton packing size / cm	N.W/G.W (kg)	Qty in 20'Gp	Qty in 40'Gp
HF121S	22.5×13.5×35.5cm(1pcs)	1.5/2.0	2,300	5,200
HF122S	29.8×13.5×35.5cm(1pcs)	3.0/3.5	1,600	3,700
HF521-HF524	30×30×60cm(1pcs)	3.5/4.0	450	1,000